

9016 SMITH MACHINE INSTALLATION INSTRUCTIONS



1. REMOVE ALL SARAN WRAP AND SHIPPING BRACKETS. RETAIN FASTENERS. INSTALL ANY FOOTPADS.
2. WITH THE RH AND LH FRAMES IN AN UPRIGHT AND STABLE POSITION, INSTALL CROSSMEMBER 9016-A03 WITH (8) .50-13X.75 BHCS. ENSURE FRAME IS NOT RACKED AND TIGHTEN.
3. CAUTION: ENSURE WEIGHT HORN ASSY END IS ORIENTATED UP TO RETAIN WEIGHTS. INSTALL (4) WEIGHT HORN ASSEMBLIES, STARTING WITH THE TOP BOLT ON EA ASSY, PASS (2) .50-13X4 BHCS THRU EA WH ASSY, FRAME, THEN WASHER UNDER NUT. ONCE BOTH BOLTS ARE INSTALLED, TIGHTEN.
4. LOWER THE BARBELL LINEAR GUIDES DOWN TO A WORKING HEIGHT. REMOVE SIDE .50-13X1.00 BHCS AND WASHERS AND RETAIN. WITH ASSISTANCE, SET IN PLACE AND ALIGN HOLES. INSTALL TOP .50-13X1.00 WITH WASHER ON EACH SIDE-SEMI TIGHT. INSTALL REMAINING. TIGHTEN ALL.

